

HANDLITE 444N

P70RPH3

Lightweight handling glove, ideal for damp and oily environments, double nitrile coating

Benefits

- Double nitrile coating for excellent water and oil resistance
- SANITIZED® treatment against the development of odour-causing bacteria
- Comfort and dexterity: very fine knitting, 18 gauge, for great glove softness

Uses

- Industry
- Maintenance
- Construction
- Public works

Packaging

- Unit of sale: pair
- Set of 5 pairs
- Box of 100 pairs

Size	Code
T7 - S	68 999 545
T8 - M	68 999 553
T9 - L	68 999 561

Size	Code
T10 - XL	68 999 588
T11 - XXL	68 999 596



Description

- Black nylon knitted glove, 18 gauge, seamless
- Smooth first nitrile coating, 3/4, blue
- Second nitrile coating with sandblast finish on palm, black
- Excellent abrasion resistance for longer glove life

Category II gloves designed to provide protection against mechanical risks only

Composition

- Material: knitted polyamide and spandex
- Coating: double nitrile coating
- Length: 23 to 27cm

Standards

EN 388
+A1



4121X

EN ISO 21420

Abrasion resistance	4/4
Cut-resistance (coup test)	1/5
Tear resistance	2/4
Puncture resistance	1/4
TDM cut	X/F
Dexterity	5/5

"X" means that the test has not been performed.